



DATI TECNICI	TECHNICAL DATA	DATOS TECNICOS	FORMPLUS - FORMPLUS/S
Alimentazione elettrica	Required power	Alimentación electrica	400 V/3+N/50Hz* 220 V/3/60 Hz
Motore ventilatore	Fan motor	Motor ventilador	1,1 kW
Res. surriscaldatore	Superheater heating el.	Resistencia recalentador	0,9 kW
Alimentazione vapore	Steam inlet	Alimentación de vapor	1/2"
Ritorno condensa	Return outlet	Retorno de condensados	1/2"
Pressione esercizio vapore	Steam working pressure	Presión de trabajo vapor	5 ÷ 6 bar - 70 ÷ 87 psi
Consumo vapore	Steam consumption	Consumo de vapor	15 ÷ 20 kg/h 33 ÷ 44 Lbs/h
Alimentazione aria	Air inlet	Alimentación de aire	1/4"
Pressione esercizio aria	Air working pressure	Presión de trabajo aire	6 ÷ 7 bar - 87 ÷ 100 psi
Consumo aria	Air consumption	Consumo de aire	10 NL/min - 0,35 cubic feet/cycle
Ingombro	Encumbrance	Medidas	1050x1260 x 2350max ÷ 1600min mm 41x50x93 max ÷ 63min in
Peso netto	Net weight	Peso netto	130 kg - 287 Lbs
Peso lordo	Gross weight	Peso bruto	160 kg - 353 Lbs
Dimensione imballo	Overall dimensions	Dimensiones embalaje	970 x 880 x 1760 mm 38 x 35 x 70 in
Volume	Vomune	Volumen	1,5 m <sup>3</sup> - 53 Ft <sup>3</sup>

\*altri voltaggi a richiesta \*other voltages by request \*otro voltaje bajo demanda

Per esigenze costruttive i dati sopracitati non sono impegnativi - For manufacturing necessities the above-mentioned specifications are not binding

PONY S.P.A.  
Via G. Di Vittorio, 8  
20065 INZAGO (MI) - ITALY  
Tel. +39 029549901  
Fax. +39 029547557  
www.ponyitaly.com - www.pony.eu  
e-mail: pony@ponyitaly.com



**PONY**  
PRESSING AND FINISHING MACHINERY